


## TYPE: H-D9000H

### Specifications


Nominal Dimension : (with sleeve)	$\Phi = 32.5 \pm 0.5\text{mm}$ $H = 59.5 \pm 0.5\text{mm}$
Applications :	Recommended discharge current 900mA to 9000mA
Nominal Voltage :	1.2V
Nominal Capacity* :	9000mAh when discharge at 1800mA(0.2C) to 1.0V at 20°C
Standard Charge :	900mA(0.1C) for 15 hrs at 20°C
Fast Charge :	9000mA (1C) with charge termination control Recommended control parameters - $\Delta V$ :10mA & $\Delta T/\Delta t$ :0.8~1°C/min Timer: 120 % nominal input
Service Life :	> 500 cycles
Continuous Overcharge :	900mA maximum permissible current No conspicuous deformation and / or leakage
Weight** :	170g
Internal Resistance** :	Max 20m $\Omega$ at 1000Hz measured within 1 hour after standard charge
Max. Charging Voltage :	1.5V at 1800mA(0.2C) charging
Ambient Temperature : Range	Standard Charge : 0°C to 45°C Fast Charge : 10°C to 45°C Discharge : -20°C to 45°C Storage : -20°C to 45°C

Note:  
\*0.2C discharge capacity after charging at 0.1C for 15 hours.  
\*\*Weight and internal impedance are for reference.




### Characteristics


#### Charge Curves ( 20°C )



#### Discharge Curves ( 20°C )



#### Temperature Characteristic



**American Toppower**

Add: 2033 Route 130, Unit N, Monmouth Junction, NJ 08852

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.